



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



Publication number:

**0 585 486 A1**

12

## EUROPEAN PATENT APPLICATION

21 Application number: 92115064.5

51 Int. Cl.<sup>5</sup>: **B23B 31/12**

22 Date of filing: 03.09.92

43 Date of publication of application:  
09.03.94 Bulletin 94/10

84 Designated Contracting States:  
**DE FR GB IT**

71 Applicant: **YUKIWA SEIKO KUBISHIKIKAI**  
Nr. 2600-1 Oaza-Chiya-Kō  
Ojiya-shi, Niigata-ken(JP)

72 Inventor: **Sakamaki, Kazuo**, c/o Yukiwa Seiko  
K.K.  
2600-1, Oaza-Chiya-Ko  
Ojiya-shi, Niigata-ken(JP)


74 Representative: **Füchsle, Klaus, Dipl.-Ing. et al**  
**Hoffmann, Eitle & Partner,**  
Patentanwälte,  
Postfach 81 04 20  
D-81904 München (DE)

54 **Chuck for tool.**

57 A chuck for a tool is provided which firmly fastens the working tool and can maintain the fastened state of the tool even when added vibration is caused during operation. A plurality of jaws (2) are obliquely provided relative to the axis of a chuck body (1,7), a grip sleeve (6) is provided close to the rear end portion of the chuck body (1,7) in unmovably fitted condition relative to the chuck body (1,7), a male screw portion (3) is formed on the outer peripheral surface of each jaw (2), a nut sleeve (4) is rotatably mounted to the chuck body (1,7), a female screw portion (5) is provided on the inner peripheral surface of the nut sleeve (4), a rotational sleeve (10) is provided in axially slidable condition to the chuck body (1,7) but unrotatably engaged with the nut sleeve (4), and the male screw portion (3) and the female screw portion (5) are engaged with each other. When said rotational sleeve (10) is rotated by hand, the jaws (2) are advanced/retracted to thereby clamp/release the tool. The rotational sleeve (10) is slidably provided in the axial direction of the chuck body (1,7) and a positioning mechanism for axial sliding movement of the rotational sleeve (10) and a rotation preventing mechanism (12,14) for preventing the rotational sleeve (10) from rotating are provided. Furthermore, positioning mechanism and said rota-

tion preventing mechanism (12,14) are located at such positions where rotational operation and positioning operation of the rotational sleeve (10) can be easily carried out with one hand grip.

FIG. 1



EP 0 585 486 A1

## BACKGROUND OF THE INVENTION

The present invention relates to a chuck for a tool such as a drill.

The present applicant discloses a chuck in Japanese Patent Application No. 63-119597 (hereinafter referred to as the prior art chuck) as shown in Fig. 9. In the prior art chuck, a buffer stop cylinder 56, which is slidable relative to a rotational sleeve 53 that is not slidable in the axial direction nor rotatable relative to the buffer stop cylinder 56 by engagement of splines 57 with spline grooves 58, is fitted to the rotatable operational sleeve 53. When the buffer stop cylinder 56 is positioned by engaging a convex portion 59, formed on the outer peripheral portion thereof, with a concave portion 60 formed on the inner peripheral surface of a grip sleeve 55, a serration portion 61 formed on the outer rear end portion of the buffer stop cylinder 56 is engaged with a serration portion 62 formed on the inner rear end portion of the grip sleeve 55, whereby the buffer stop cylinder 56 is kept unrotatable relative to the grip sleeve 55, and hence the rotational sleeve 53 is kept unrotatable also relative to the grip sleeve 55, thereby preventing the rotational sleeve 53 from being rotated relative to the chuck body 52 and ensuring the fastening effect of a working tool 54 with jaws 51.

It has been however found through various experiments that the prior art chuck has disadvantages or inconvenience in use. Namely, since the buffer stop cylinder 56 is provided around over the outer peripheral surface of the rotational sleeve 53 which is gripped by a user's hand and on which his palm contacts, it would be inconvenient to carry out the rotational operation of the rotational sleeve 53, and also after the rotational sleeve 53 has been rotated to thereby fastening a working tool 54 with jaws 51, a user has to let go his grip off the rotational sleeve 53 and slide the buffer stop cylinder 56, thus two actions are required on his hand's movement, which reduces the work efficiency.

A primary object of the invention is to provide a chuck for a tool which can overcome the above-noted disadvantages.

## SUMMARY OF THE INVENTION

An object of this invention is to eliminate the disadvantages of the prior art chuck for a tool and to provide a chuck for a tool, of which rotational sleeve can be prevented from being rotated relative to the chuck body even when a buffer stop cylinder being eliminated therefrom. According to the invention, to accomplish this object, there is provided a chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck

body, a grip sleeve is provided close to the rear end portion of the chuck body in unrotatable condition relative to the chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to the chuck body, a female screw portion is provided on the inner peripheral surface of the nut sleeve, and the male screw portion and the female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to the nut sleeve and whereby the rotational sleeve is rotated to thereby advance/retract the jaws, the chuck comprising the improvement wherein the rotational sleeve is slidably provided in the axial direction; a positioning mechanism for restricting the rotational sleeve from sliding in the axial direction and a rotation preventing mechanism for preventing the rotational sleeve from rotating are provided; and the positioning mechanism and the rotation preventing mechanism are located at positions where rotational operation of the rotational sleeve is not obstructed by the positioning mechanism and the rotation preventing mechanism.

According to another aspect of the invention, there is provided a chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of the chuck body in unrotatable condition relative to the chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to the chuck body, a female screw portion is provided on the inner peripheral surface of the nut sleeve, and the male screw portion and the female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to the nut sleeve and whereby the rotational sleeve is rotated to thereby advance/retract the jaws, the chuck comprising the improvement wherein the rotational sleeve is slidably provided in the axial direction; a plurality of circumferential concave portions are formed on the inner peripheral surface close to the front end of the rotational sleeve and a ball which is retractable/projectable by a suitable means and engageable with the circumferential concave portions are provided on the outer peripheral surface close to the front end of the chuck body to thereby constitute a positioning mechanism; and a serration is formed on the outer peripheral surface close to the rear end of the rotational sleeve and another serration is formed on the inner peripheral surface close to the front side of the grip sleeve and both serrations are engaging each other to thereby constitute a rotation preventing mechanism.

According to another aspect of the invention there is provided chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided

close to the rear end portion of the chuck body in unrotatable condition relative to the chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to the chuck body, a female screw portion is provided on the inner peripheral surface of the nut sleeve, and the male screw portion and the female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to the nut sleeve and whereby the rotational sleeve is rotated to thereby advance/retract the jaws, the chuck comprising the improvement wherein the rotational sleeve is slidably provided in the axial direction; a sleeve is provided close to the rear end of the rotational sleeve; a convex portion is provided on the outer peripheral surface of the sleeve and a concave portion which is engageable with the convex portion is provided on the inner peripheral surface close to the rear end of the grip sleeve; and a serration is provided on the outer peripheral surface close to the rear end of the rotational sleeve, which is engageable with another serration provided on the inner peripheral surface close to the front end of the grip sleeve.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings;

Fig. 1 is a fragmentary longitudinal cross-sectional view of a chuck according to the present invention;

Fig. 2 is a fragmentary longitudinal cross-sectional view of another state of the chuck shown in Fig. 1;

Fig. 3 is a fragmentary sectional view taken on the line A-A of Fig. 2;

Fig. 4 is a cross-sectional view taken on the line B-B of Fig. 2;

Fig. 5 is a fragmentary longitudinal cross-sectional view of a chuck according to another embodiment of the invention;

Fig. 6 is a fragmentary longitudinal cross-sectional view of a chuck according to still another embodiment of the invention;

Fig. 7 is a fragmentary longitudinal cross-sectional view of a chuck according to still another embodiment of the invention;

Fig. 8 is a fragmentary longitudinal cross-sectional view of a chuck according to still another embodiment of the invention; and

Fig. 9 is a fragmentary longitudinal cross-sectional view of a chuck according to the prior art.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described with reference to the accompanying drawings

which show some of the various embodiments of the invention, in which are shown variety of positions where a rotation preventing mechanism 8 and the positioning mechanism 9 of the axial sliding of a rotational sleeve are located. Figs. 1 to 4 show a first embodiment in which the rotation preventing mechanism 8 is provided between the rotational sleeve 10 and the grip sleeve 6, and the positioning mechanism 9 is provided between the rotational sleeve 10 and the chuck body 1. Fig. 5 shows another embodiment in which the rotation preventing mechanism 8 and the positioning mechanism 9 are provided between the rotational sleeve 10 and the grip sleeve 6. Fig. 6 shows still another embodiment in which the rotation preventing mechanism 8 is provided between the rotational sleeve 10 and the grip sleeve 6, and the positioning mechanism 9 is provided between the rotational sleeve 10 and a sleeve 30. Fig. 7 shows a fourth embodiment in which the rotation preventing mechanism 8 is provided between the rotational sleeve 10 and the chuck body 1 on the position close to the front end, and the positioning mechanism 9 is provided between the rotational sleeve 10 and the sleeve 30 as similarly to Fig. 6. Fig. 8 shows a fifth embodiment in which the rotation preventing mechanism 8 is provided between the rotational sleeve 10 and the sleeve 30, and the positioning mechanism 9 is provided between the rotational sleeve 10 and the sleeve 30 as similarly to Fig. 6.

The types of the devices according to the invention are classified as described above. However, among these types, there is a common feature that the rotational sleeve 10 can be kept unrotatable relative to a fastening members 7 (corresponding to the chuck body 1 and the grip sleeve 6) and the positioning of the axial slide movement of the rotational sleeve 10 can be done, both by one gripping operation of the rotational sleeve 10, without otherwise required buffer stop cylinder operation for the prior art chuck.

The first embodiment of the invention will now be described.

Radially divided three jaws 2 are slidably and obliquely provided in a chuck body 1. A nut sleeve 4 which is divided for assembly is rotatably mounted on the chuck body 1. A shape retaining hoop 20 is pressingly fitted around the outer peripheral surface of the nut sleeve 4 for retaining a shape of the nut sleeve 4 in a unit. A female screw portion 5 of the nut sleeve 4 is engaged with a male screw portion 3 of the jaws 2.

A concave portion 16 is formed on the outer surface close to the front end portion of the chuck body 1. A spring 18 is provided in the concave portion 16. A ball 17 is disposed in the concave portion 16, the ball 17 partially projecting by the spring 18 to either of a plurality of circumferential

concave portions 15 provided on the inner peripheral surface close to the front end of the operational sleeve 10.

The rear end portion of the rotational sleeve 10, which is made of synthetic resin, is inserted into a grip sleeve 6 so as to be axially slidable to the grip sleeve 6, that is, in the axial direction relative to the chuck body 1. A serration 12 having convex portions 11 is provided on the outer peripheral surface of the rear end portion of the rotational sleeve 10.

Reference numeral 21 denotes a bearing seat, numeral 22 denotes a bearing ball, numeral 23 denotes a stop ring, and numeral 29 denotes an engagement portion for transmitting the rotation torque of the rotational sleeve 10 to the nut sleeve 4.

Reference numeral 10' denotes a groove in an axial direction on which the shape retaining hoop 20 is fitted, and the rotational sleeve 10 slides between said groove 10' and said stop ring 23 in the axial direction.

The grip sleeve 6 is fixed to the chuck body 1 under the condition that the grip sleeve 6 is prevented from rotating relative to the chuck body 1. A serration 14 having convex portions 13 is provided on the inner peripheral surface of the front end portion of the grip sleeve 6.

With the above-described arrangement of the first embodiment, when the grip sleeve 6 is gripped by the user's hand and the rotational sleeve 10 is rotated by the other hand, the nut sleeve 4 is rotated. The jaws 2 are obliquely slid forward by the threaded engagement action between the nut sleeve 4 and the jaws 2, clamping tool 19. Also, when the rotational sleeve 10 is rotated in the reverse direction, the jaws 2 are obliquely slid backward, releasing the tool 19.

After the tool 19 has been fastened by the fastening rotation of the rotational sleeve 10 and when the rotational sleeve 10 is slid rearward as shown in Fig. 2, the edge of the hoop 20 hits the end of the groove 10' and simultaneously the ball 17 provided in the chuck body 1 projects into the concave portion 15 formed on the inner surface of the front end of the rotational sleeve 10, and at the same time, the serration 12 and the serration 14 are engaged with each other. As a result, the rotational sleeve 10 is positioned in the axial direction relative to the chuck body 1, and the rotational sleeve 10 is kept unrotatable relative to the chuck body 1. Accordingly, it is possible to positively maintain the clamped state of the tool 19 even when some vibration caused in use of the chuck.

If the rotational sleeve 10 is slid forward, the engagement between the serration 12 and the serration 14 is released and the rotational sleeve 10 can be rotated in reverse to thereby release the

tool 19, and in this action, the forward positioning of the rotational sleeve 10 is done by the ball 17 to project into the rear side concave 15 and by the hitting of the stop ring 23 to the hoop(20)'s rear end edge.

Fig. 5 shows a second embodiment of the invention, in which a sleeve 24 which is made of synthetic resin, a convex portion 24' of the end portion serves as the stop ring 23, and the backward positioning of the axial slide movement of the rotational sleeve 10 is done by hitting of the hoop(20)'s top edge to the end of the groove 10' as well as engagement of the sleeve(24)'s convex portion 25 into the concave portion 26 formed on the inner peripheral surface of the grip sleeve 6. The rotation preventing mechanism 8 of the second embodiment is the same as that of the first embodiment. Namely, the rotational sleeve 10 is kept unrotatable relative to the chuck body 1 and grip sleeve 6 through the engagement of the serration 12 and the serration 14. The other structures and the associated effects are the same as those of the first embodiment. Slits 27 are formed for the purpose of imparting flexibility to the sleeve 24.

Incidentally, in the second embodiment shown in Fig. 5, the same reference numerals are used to denote the like members and components of the first embodiment.

A third embodiment shown in Fig. 6 has the common feature with the first embodiment in the same meaning. In the third embodiment, a sleeve 30 made of synthetic resin is fixed to the chuck body 1 being clamped between the chuck body 1 and the grip sleeve 6. Convex portions 31 formed at an outer peripheral portions of the ends of projections 30' located at the opposite portions formed on the circumferential edge line of the sleeve 30 are engaged with associated concave portions 28 provided on the inner peripheral surface of the end portion of the rotational sleeve 10 for positioning the axial slide movement of the rotational sleeve 10 relative to the grip sleeve 6, i. e., the chuck body 1. Other associated mechanisms for the positioning of the slide movement of the rotational sleeve are the same as for the first embodiment. And also the structure of the rotation preventing mechanism 8 is the same as that of the first embodiment.

The other structures and effects are the same as those of the first embodiment. Also, in the third embodiment, the same reference numerals are used to denote like members and components of the first embodiment.

Fig. 7 shows a fourth embodiment of the invention, in which the positioning mechanism 9 of the axial slide movement of the rotational sleeve 10 is the same as that of the third embodiment. The rotation preventing mechanism 8 is the same as the other embodiments in structure but is different

from that of the other embodiments in position. In the fourth embodiment, a serration 32 is formed on the outer peripheral surface of the front end of the chuck body 1, which engages with a serration 33 formed on the inner peripheral surface of the front end portion of the rotational sleeve 10.

The other structures and effects are the same as those of the first embodiment. Also, in the fourth embodiment, the same reference numerals are used to denote the like members and components as those of the first embodiment.

Fig. 8 shows a fifth embodiment of the invention, in which the positioning mechanism 9 of the axial slide movement of the rotational sleeve 10 is the same as that of the third embodiment. The rotation preventing mechanism 8 is comprised of serrations 35 and 36 engaged each other provided between the rear end portion of the inner peripheral surface of the rotational sleeve 10 and the outer peripheral surface of the sleeve 34.

The other structures and effects are the same as that of the first embodiment, and also in the fifth embodiment, the same reference numerals are used to denote like members and components of the first embodiment.

In the chuck of the foregoing embodiments, the screw pitch of the male screw portion 3 of the jaws 2 and the female screw portion 5 of the nut sleeve 4 is small, and hence, one-pitch axial movement of the jaws 2 is small. However, since the rotational sleeve 10 is rotated by a user's hand, the rotating operation of the rotational sleeve 10 is very easy. Rather, there is a merit that a strong propelling force can be generated because of this small screw pitching.

With the above-described arrangement of the invention, it is possible to provide a chuck for a tool of which tool clamping and releasing operation can be done more easily being compared to the prior art chuck since a buffer stop cylinder 56 doesn't exist (Clamping of a tool 19 is done by gripping and rotating the rotational sleeve 10 to thereby advance the jaws 2, and the rotational sleeve 10 can be slid without changing the gripping to thereby make the rotational sleeve 10 to be unrotatable.), and which can maintain the clamping state of the tool without being loosened by a vibration of the tool during the use.

Reference signs in the claims are intended for better understanding and shall not limit the scope.

## Claims

1. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said

chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a positioning mechanism for restricting said rotational sleeve from sliding in the axial direction and a rotation preventing mechanism for preventing said rotational sleeve from rotating are provided; and said positioning mechanism and said rotation preventing mechanism are located at positions where rotational operation of said rotational sleeve is not obstructed by said positioning mechanism and said rotation preventing mechanism.

2. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a plurality of circumferential concave portions are formed on the inner peripheral surface close to the front end of said rotational sleeve and a ball which is retractable/projectable by a suitable means and engageable with said circumferential concave portions are provided on the outer peripheral surface close to the front end of said chuck body to thereby constitute a positioning mechanism; and a serration is formed on the outer peripheral surface close to the rear end of said rotational sleeve and another serration is formed on the inner peripheral surface close to the front side of said grip sleeve and both serrations are engaging each other to thereby constitute a rotation preventing mechanism.

3. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a sleeve is provided close to the rear end of said rotational sleeve; a convex portion is provided on the outer peripheral surface of said sleeve and a concave portion which is engageable with said convex portion is provided on the inner peripheral surface close to the rear end of said grip sleeve; and a serration is provided on the outer peripheral surface close to the rear end of said rotational sleeve, which is engageable with another serration provided on the inner peripheral surface close to the front end of said grip sleeve.
4. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a concave portion is provided on the inner peripheral surface close to the rear end of said rotational sleeve, a sleeve is provided close to the front side of said grip sleeve, and a convex portion which is engageable with said concave portion is provided on the outer peripheral surface of said sleeve to thereby constitute a positioning mechanism; and a serration is provided on the outer peripheral surface close to the rear end

of said rotational sleeve, which is engageable with another serration provided on the inner peripheral surface close to the front end of said grip sleeve to constitute a rotation preventing mechanism.

5. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a concave portion is provided on the inner peripheral surface close to the rear end of said rotational sleeve, a sleeve is provided close to the front side of said grip sleeve, and a convex portion which is engageable with said concave portion is provided on the outer peripheral surface of said sleeve; and a serration is provided on the inner peripheral surface close to the front end of said rotational sleeve, which is engageable with another serration provided on the outer peripheral surface close to the front end of said chuck body.
6. A chuck for a tool, wherein a plurality of jaws are obliquely provided relative to the axis of the chuck body, a grip sleeve is provided close to the rear end portion of said chuck body in unrotatable condition relative to said chuck body, a male screw portion is formed on the outer peripheral surface of each jaw, a nut sleeve is fitted to said chuck body, a female screw portion is provided on the inner peripheral surface of said nut sleeve, and said male screw portion and said female screw portion are engaged with each other, and the rotational sleeve is engaged unrotatably to said nut sleeve and whereby said rotational sleeve is rotated to thereby advance/retract said jaws, said chuck comprising the improvement wherein said rotational sleeve is slidably provided in the axial direction; a concave portion is provided on the inner peripheral surface close to the rear end of said rotational sleeve, a sleeve is provided close to the front side of

said grip sleeve, and a convex portion which is engageable with said concave portion is provided on the outer peripheral surface of said sleeve to thereby constitute a positioning mechanism; and a serration is provided on the inner peripheral surface close to the rear end of said rotational sleeve, which is engageable with another serration provided on the outer peripheral surface of the sleeve to constitute a rotational preventing mechanism.

7. A chuck for a tool, comprising:
  - a chuck body (1, 7) having a grip sleeve (6) which is gripped by a user's hand;
  - a chucking means (2) for clamping a tool;
  - a rotational sleeve means (10) for transmitting a rotational force, applied by the user, to the nut sleeve (4) to advance/retract the chucking means (2), said rotational sleeve means being slidably movable in the axial direction relative to said chuck body;
  - a rotation preventing means (12, 14) for preventing said rotation of said rotational sleeve means;
  - a slide restricting means (15, 17) for restricting the axial sliding movement of said rotational sleeve means.
8. The chuck according to claim 7, wherein said rotation preventing means is not provided in a position where said rotation preventing means obstructs the rotational operation of said rotational sleeve means.
9. The chuck according to claim 7, wherein said slide restricting means is not provided in a position where said slide restricting means obstructs the sliding movement of said rotational sleeve means.
10. The chuck according to claim 8, wherein said rotation preventing means is located between said grip sleeve and said rotational sleeve means.
11. The chuck according to claim 8, wherein said rotation preventing means is located between said chuck body and said rotational sleeve means.
12. The chuck according to claim 8, wherein said rotation preventing means includes a sleeve connected to said grip sleeve, said sleeve having an engagement portion engageable with said rotational sleeve means.
13. The chuck according to claim 9, wherein said slide restricting means includes a ball which is

retractable/projectable relative to said chuck body, said ball having an engagement portion engageable with said rotational sleeve means.

14. The chuck according to claim 9, wherein said slide restricting means includes a sleeve movable together with said rotational sleeve means, said sleeve having an engagement portion engageable with said grip sleeve.
15. The chuck according to claim 9, wherein said slide restricting means includes a sleeve connected to said grip sleeve, said sleeve having an engagement portion engageable with said rotational sleeve means.

FIG. 1





FIG. 2





1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
84



•

FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9  
PRIOR ART





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number

EP 92 11 5064

### DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	GB-A-2 154 927 (RÖHM) * page 4, line 16 - line 35; figures 1-2A * --- A EP-A-0 340 310 (SAKAMAKI) --- A EP-A-0 300 375 (SAKAMAKI) --- A DE-A-3 540 223 (RÖHM) --- A GB-A-2 034 210 (RÖHM) -----	1,3,7	B23B31/12
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			B23B
The present search report has been drawn up for all claims			
Place of search	Date of completion of the search	Examiner	
THE HAGUE	11 MAY 1993	BOGAERT. F.L.	
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document			

EPO FORM L50 (01.82 (P0401)